


Overview


Compaq Evo Notebook N620c

HP recommends Microsoft®
Windows® XP Professional



1. Color Display
2. Stereo Speakers
3. Power Switch
4. RJ-11 (Modem)
5. MultiBay
6. Kensington Lock
7. Dual Pointing Devices
8. Audio-In
9. Headphone-Out

10. Volume Controls
11. Infrared Port
12. System LEDs
13. PC Card Slots (2)
14. Memory Access Door
15. Hard Drive
16. Keyboard LEDs
17. Suspend Button
18. Easy Access Internet Buttons



1. S-Video (TV Out)
2. VGA
3. Serial
4. RJ-45 (NIC)

5. USB (2)
6. Parallel
7. PS/2
8. DC In

Overview

At A Glance

- Intel® Pentium® M Processors at 1.3, 1.4, 1.5, or 1.6. GHz
- Microsoft® Windows® XP Professional or Microsoft Windows 2000
- ATI Mobility Radeon 7500 Graphics Controller with 32 MB of DDR video RAM.
- 14.1-inch SXGA+ or 14.1-inch XGA display
- Configurations as light as 4.8 lb/2.2 kg weight
- 1.2 in/3.048 cm thin
- 256 MB DDR RAM (266 MHz), upgradeable to 2048 MB
- Up to 60-GB 5400rpm, user-removable hard drives
- Full-size keyboard
- Includes three-year, Worldwide Limited Warranty. Next-day onsite service or one-year warranty is also available.

What's New

- Intel Pentium M Processors
- Up to 6 hours of battery life
- Gigabit Ethernet NIC
- Common Port Replicator and Advanced Port Replicator with Gigabit NIC pass-through
- 802.11b Wireless LAN MultiPort now with Cisco LEAP support
- New Security features: Pre-boot BIOS Smart Card authentication and HP's ProtectTools Smart Card Security Manager Software
- USB port can power External MultiBay option
- HP's Mobile Printing driver makes on-the-go printing quick and easy

Standard Features

Processors

1.6-GHz Intel Pentium-M Processor with 400-MHz Front Side Bus and 1024-KB L2 cache
1.5-GHz Intel Pentium-M Processor with 400-MHz Front Side Bus and 1024-KB L2 cache
1.4-GHz Intel Pentium-M Processor with 400-MHz Front Side Bus and 1024-KB L2 cache
1.3-GHz Intel Pentium-M Processor with 400-MHz Front Side Bus and 1024-KB L2 cache

NOTE: Intel Pentium-M Processors support enhanced Intel SpeedStep technology.

Operating System

One of the following

Microsoft Windows XP Professional or Microsoft Windows 2000.
Microsoft Windows XP Home (English only).

NOTE: Driver support available for Microsoft Windows 98 SE and Microsoft Windows NT 4.0 in June 2003

Display

Internal

14.1-inch color TFT SXGA+ with 1400 x 1050 resolution (up to 16.7M colors internal)

14.1-inch color TFT XGA with 1024 x 768 resolution (up to 16.7M colors internal)

External

Up to 32-bit per pixel color depth

Supports 640 x 480, 800 x 600, 1024 x 768, 1280 x 1024, 1400 x 1050, 1600 x 1200, or 2048 x 1536 resolutions up to 160-Hz refresh rate, dependent upon monitor capability, resolution and color depth settings

Memory

Standard

256-MB 266-MHz SDRAM DDR SDRAM (256-MB SODIMM in slot 1)

Maximum

2-GB 266-MHz SDRAM DDR SDRAM (1024-MB SODIMMs in slots 1 and 2)

NOTE: Due to the non-industry standard nature of some third-party memory modules, we recommend Compaq branded memory to ensure compatibility.

Communications

10/100/1000 NIC is integrated on the system board

56K (V.92) modem with digital line guard

NOTE: Designed only to allow faster downloads from V.90/V.92 compliant sources. Maximum achievable download transmission rates currently do not reach 56 KB/s, and will vary with line conditions.

NOTE: Modem availability is subject to country regulatory approval.

Keyboard

The 101/102-key compatible keyboard features an industry standard, full-width layout with desktop keyboard features, such as the isolated inverted-T cursor control keys, 3x2 editing keys, both left and right control and alt keys, and 12 function keys. The US layout has 84 keys and the International layout 85 keys. Other features include an integrated numeric keypad, hotkeys for instant access to power conservation, volume, brightness, and other features, 19.05 mm x 19.05 mm key pitch (center-to-center spacing), 2.5 mm stroke, comfort-dished keycaps, and bright key legends for improved visibility in low light conditions.

Easy Access Internet Buttons

The Evo Notebook N620c comes with four programmable Easy Access Buttons to provide one-touch access to helpful Compaq information, favorite Internet destinations, files, or applications.

Standard Features

Pointing Device	Dual pointing devices (both Pointstick and Touchpad). Also available with Pointstick only or touchpad only.	
PC Card Slots	Two Type II/One Type III PC Card Slots which support both 32-bit CardBus and 16-bit PC Cards	
Storage	Diskette Drives	Optional 1.44 MB Diskette Drive
	Hard Drives	60-GB 5400 rpm SMART Hard Drive 40-GB 5400 rpm SMART Hard Drive 30-GB 4200 rpm SMART Hard Drive
	Optical Drives	24X/10X/24X/8X DVD/CD-RW Combo Drive (CD-R/CD-RW/CD-ROM/DVD-ROM) 24X/8X/24X CD-RW Drive (CD-R/CD-RW/CD-ROM) 8X DVD-ROM Drive 24X CD-ROM Drive
	NOTE: Evo Notebook N620c hard drives are customer removable and will withstand multiple insertion/removal cycles.	
Multimedia	Compaq Premier-Sound enhanced stereo audio system Integrated 16-bit stereo audio Integrated stereo speakers and microphone External Hardware volume controls Headphone-out Microphone in CD, DVD, CDRW, or DVD/CDRW drive Software MPEG1, MPEG2 and DVD support DVD Movie Playback Software (on DVD and DVD/CD-RW models) S-video TV-out port 4X AGP graphics 32 MB of DDR VRAM	
Interfaces	MultiPort	1
	PC Card	2 Type II/1 Type III
	Enhanced Parallel EPP/ECP	1 (can be used to connect external diskette drive)
	Serial Port	1
	S-video TV-out connector	1 (NTSC/PAL)
	External Monitor	1
	PS/2 External Keyboard/Pointing Device	1 Supports Y-cable to attach both Keyboard and Mouse simultaneously
	Docking Connector	1
	Headphone/Line-out	1
	Microphone/Line- in	1
	DC Power	1
	RJ-11 (modem)	1
	RJ-45 (NIC)	1
	Infrared Port	1 (4 Mb/s support) (IrDA 4 MB compliant. IR performance will vary depending on performance of IR peripherals and application used.)

Standard Features

USB Port (USB 2.0) 2 (one port can power the External MultiBay option)
LED status indicators 7

Graphics

ATI Mobility Radeon 7500 4X AGP graphics controller with 32-MB DDR VRAM
Hardware support for DirectX 7.0
ATI Powerplay Technology

Software

Installed Software

Intervideo WinDVD Player*

Adobe Acrobat Reader

HP Mobile Printing for Notebooks

NOTE: The HP mobile printing driver allows you to print quickly and easily to almost any network postscript printer. Print your document to the Mobile Printer Driver and enter the IP address of a nearby network printer when prompted, and your document prints to it. No driver installation or setup is required.

Compaq Wireless LAN MultiPort W200 Software

Compaq Bluetooth Software*

Broadcom Netxtreme Gigabit Ethernet Drivers

Synaptics Touchpad Driver

Intel SpeedStep Technology Applet (Windows 2000 only)*

Altiris eXpress Client Win32*

Insight Management Agents*

Diagnostics for Windows*

Remote Diagnostics Enabling Agents*

Compaq Easy Access Button Software

Compaq Help and Support (XP Only)

Compaq Info Center (XP Only)

Software on CD

Compaq Quick Restore System Recovery

Roxio Easy CD Creator 5 (on CDRW and DVD/CDRW models)

Compaq Evo N620c Documentation Library

Software on www.hp.com

ProtectTools Smart Card Security Manager (www.hp.com/security)

Supporting software and drivers for Windows 98 SE and Windows NT 4.0.**

Comprehensive driver, BIOS, and software downloads

Compaq Evo N620c Models with Microsoft Office XP Professional or Office XP Small Business Edition are available in North America at www.hp.com for customers with less than 500 employees.

* Software is loaded on the HDD and must be installed by running the Setup Compaq Software utility.

** Available 2Q03.

System Recovery

Each unit is shipped with a CD kit for quick recovery (erases hard disk and restores manufacturer installed image) and software recovery (installs only selected standard software)

Standard Features

Intelligent Manageability

Intelligent Manageability, a key component of HP PC Lifecycle Solutions, is the broad set of manageability features found on Evo Client and ProLiant server products. These manageability features on PC clients comply with industry standards, such as DMI, SMBIOS, PXE, and WBEM and Wired for Management, while pioneering new ground in client manageability. HP introduced the industry's first line of manageable clients in 1995 and has been driving the industry ever since. With HP's lifecycle management philosophy, enterprises have all of the pieces for end-to-end management and proven tools for hassle-free management of PCs. The combination of these tools significantly lowers the Total Cost of Ownership of managing the computing environment. Intelligent Manageability offers solutions in the areas of Initial Configuration and Deployment, Asset Tracking and Security, Software Updating and Management, and Fault Notification and Recovery. More information is available at the following web sites: <http://www.compaq.com/im>; <http://www.compaq.com/easydeploy>; <http://www.compaq.com/solutions/pcsolutions>.

NOTE: These Web sites are available in English only.

Security

Configuration Control Hardware
Memory Change Alert
Ownership Tag
Set-up Password
Power-On Password
DriveLock
Enabled for PC Smart Card options
Kensington Lock
Pre-boot BIOS authentication of smart card capability

Power Supply

External 65 W AC adapter, 6-foot/1.8-meter power cord included.
Total length including External AC adapter is 12 feet/3.66 meter.

Battery

The Evo Notebook N620c provides up to 6 hours of battery life using the standard 8-cell Lithium-ion battery and up to 10 hours with the optional MultiBay battery.

NOTE: Actual results may vary with product model, configuration, and individual usage. Hewlett-Packard testing of an N620c with an Intel Pentium-M 1.4 GHz CPU, Windows XP Pro, 14.1" XGA LCD, 256-MB RAM, 40-GB HDD, DVD, Lithium-ion primary battery, and NIC/modem, achieved an overall Business Winstone 2002 BatteryMark score of 6h 8m Business Winstone 2002 BatteryMark Version 1.0 units. Winstone® is a registered trademark and BatteryMark™ is a trademark of Ziff Davis Publishing Holdings Inc. in the U.S. and other countries. Copyright 2002 Ziff Davis Media Inc. All Rights Reserved. System parameters followed test recommendations: panel brightness 50%, power management scheme - Laptop/Portable, hard drive, standby and video timers set to never. This N620c configuration with an optional Lilon MultiBay battery substituted for the DVD device achieved an overall Business Winstone 2002 BatteryMark score of 10h 45m Business Winstone 2002 BatteryMark Version 1.0 units.

Battery Re-Charge Time	System in OFF mode or Standby	2 hours
	System ON (depending on system power consumption)	2-5 hours

Power Conservation

Supports enhanced Intel SpeedStep Technology (allows a Battery Optimized Mode, Maximum Performance Mode, or Automatic mode)
Hibernation
Instant-on via Standby
Pop-ups with three presets
One custom level of power conservation
ACPI compliant

Standard Features

MultiBay Devices

MultiBay devices may be swapped with the system powered (hot) under Windows 2000, or Windows XP Professional (except secondary hard drive). MultiBay devices can be swapped with system power off under any supported operating system.

MultiPort

MultiPort is a flexible, innovative solution providing customers the ability to connect to their choice of wireless standards such as 802.11b or Bluetooth. This can be achieved by simply changing out the high-performance wireless module, which is integrated into the top of the notebook. The award-winning MultiPort offers a cost effective means to migrate to future wireless standards as they become available.

Docking

NEW! Port Replicator and Advanced Port Replicator with Gigabit NIC pass-through. The new models of the port replicator and advanced port replicator provide simple and convenient port management and pass-through of Fast Ethernet or Gigabit NIC. Compatible across multiple products.

Service and Support


HP Services includes a Three-year, Worldwide Limited Warranty, pick-up or carry-in and toll-free 7 x 24 hardware technical phone support. On-site service or a one-year warranty are also available.

NOTE: Certain restrictions and exclusions apply. Consult the HP Customer Support Center for details.

http://wwss1pro.compaq.com/support/warranty_upgrades/product_specific_warranty.asp

Naming Convention

The Etymology of a Model name:



Standard Features

Models

N620cP160P460WG512
DE273A#xxx

Processor	1.6-GHz Intel Pentium-M processor with 400-MHz Front Side Bus
Operating System	Microsoft Windows 2000
Display	14.1-inch color TFT SXGA+ with 1400 x 1050 resolution (up to 16.7M colors internal)
Cache Memory	1024 KB L2 cache
Memory	Standard 512-MB 266-MHz SDRAM DDR SDRAM (256-MB SODIMM in slot 1) Maximum 2-GB 266-MHz SDRAM DDR SDRAM (512-MB SODIMM in slots 1 and 2)
Hard Drive	60-GB 5400 rpm SMART Hard Drive
Video Memory	32 MB
Optical Drive	24X DVD/CDRW
Graphics	ATI Mobility Radeon 7500 4X AGP graphics controller with 32 MB DDR VRAM
Audio	Compaq Premier- Sound enhanced stereo audio system
Communications	56K (V.92) modem, integrated 10/100/1000 NIC
Pointing Device	Dual pointing devices (both Pointstick and Touchpad)
Battery	8-cell 4.4 Ah
Warranty	3/3/0

N620cP160P460WG510
DE272A#xxx

Processor	1.6-GHz Intel Pentium-M processor with 400-MHz Front Side Bus
Operating System	Microsoft Windows XP Professional
Display	14.1-inch color TFT SXGA+ with 1400 x 1050 resolution (up to 16.7M colors internal)
Cache Memory	1024 KB L2 cache
Memory	Standard 512-MB 266-MHz SDRAM DDR SDRAM (256-MB SODIMM in slot 1) Maximum 2-GB 266-MHz SDRAM DDR SDRAM (512-MB SODIMM in slots 1 and 2)
Hard Drive	60-GB 5400 rpm SMART Hard Drive
Video Memory	32 MB
Optical Drive	24X DVD/CDRW
Graphics	ATI Mobility Radeon 7500 4X AGP graphics controller with 32 MB DDR VRAM
Audio	Compaq Premier-Sound enhanced stereo audio system
Communications	56K (V.92) modem, integrated 10/100/1000 NIC
Pointing Device	Dual pointing devices (both Pointstick and Touchpad)
Battery	8-cell 4.4 Ah
Warranty	3/3/0

Standard Features

N620cP150P460WG512 DE271A#xxx	Processor	1.5-GHz Intel Pentium-M processor with 400-MHz Front Side Bus
	Operating System	Microsoft Windows 2000
	Display	14.1-inch color TFT SXGA+ with 1400 x 1050 resolution (up to 16.7M colors internal)
	Cache Memory	1024 KB L2 cache
	Memory	Standard 512-MB 266-MHz SDRAM DDR SDRAM (256-MB SODIMM in slot 1) Maximum 2-GB 266-MHz SDRAM DDR SDRAM (512-MB SODIMM in slots 1 and 2)
	Hard Drive	60-GB 5400 rpm SMART Hard Drive
	Video Memory	32 MB
	Optical Drive	24X DVD/CDRW
	Graphics	ATI Mobility Radeon 7500 4X AGP graphics controller with 32 MB DDR VRAM
	Audio	Compaq Premier-Sound enhanced stereo audio system
	Communications	56K (V.92) modem, integrated 10/100/1000 NIC
	Pointing Device	Dual pointing devices (both Pointstick and Touchpad)
	Battery	8-cell 4.4 Ah
Warranty	3/3/0	

N620cP150P460WG510 DE270A#xxx	Processor	1.5-GHz Intel Pentium-M processor with 400-MHz Front Side Bus
	Operating System	Microsoft Windows XP Professional
	Display	14.1-inch color TFT SXGA+ with 1400 x 1050 resolution (up to 16.7M colors internal)
	Cache Memory	1024 KB L2 cache
	Memory	Standard 512-MB 266-MHz SDRAM DDR SDRAM (256-MB SODIMM in slot 1) Maximum 2-GB 266-MHz SDRAM DDR SDRAM (512-MB SODIMM in slots 1 and 2)
	Hard Drive	60-GB 5400 rpm SMART Hard Drive
	Video Memory	32 MB
	Optical Drive	24X DVD/CDRW
	Graphics	ATI Mobility Radeon 7500 4X AGP graphics controller with 32 MB DDR VRAM
	Audio	Compaq Premier-Sound enhanced stereo audio system
	Communications	56K (V.92) modem, integrated 10/100/1000 NIC
	Pointing Device	Dual pointing devices (both Pointstick and Touchpad)
	Battery	8-cell 4.4 Ah
Warranty	3/3/0	

Standard Features

N620cP140X440VJ252
DE269A#xxx

Processor	1.4-GHz Intel Pentium-M processor with 400-MHz Front Side Bus
Operating System	Microsoft Windows 2000
Display	14.1-inch color TFT XGA with 1024 x 768 resolution (up to 16.7M colors internal)
Cache Memory	1024 KB L2 cache
Memory	Standard 256-MB 266 MHz SDRAM DDR SDRAM (256-MB SODIMM in slot 1) Maximum 2-GB 266-MHz SDRAM DDR SDRAM (512-MB SODIMM in slots 1 and 2)
Hard Drive	40-GB 5400 rpm SMART Hard Drive
Video Memory	32 MB
Optical Drive	8X DVD
Graphics	ATI Mobility Radeon 7500 4X AGP graphics controller with 32 MB DDR VRAM
Audio	Compaq Premier-Sound enhanced stereo audio system
Communications	56K (V.92) modem, integrated 10/100/1000 NIC
Pointing Device	Dual pointing devices (both Pointstick and Touchpad)
Battery	8-cell 4.4 Ah
Warranty	3/3/0

N620cP140X440VJ250
DE268A#xxx

Processor	1.4-GHz Intel Pentium-M processor with 400-MHz Front Side Bus
Operating System	Microsoft Windows XP Professional
Display	14.1-inch color TFT XGA with 1024 x 768 resolution (up to 16.7M colors internal)
Cache Memory	1024 KB L2 cache
Memory	Standard 256-MB 266 MHz SDRAM DDR SDRAM (256-MB SODIMM in slot 1) Maximum 2-GB 266-MHz SDRAM DDR SDRAM (512-MB SODIMM in slots 1 and 2)
Hard Drive	40-GB 5400 rpm SMART Hard Drive
Video Memory	32 MB
Optical Drive	8X DVD
Graphics	ATI Mobility Radeon 7500 4X AGP graphics controller with 32 MB DDR VRAM
Audio	Compaq Premier-Sound enhanced stereo audio system
Communications	56K (V.92) modem, integrated 10/100/1000 NIC
Pointing Device	Dual pointing devices (both Pointstick and Touchpad)
Battery	8-cell 4.4 Ah
Warranty	3/3/0

Standard Features

N620cP140X440VG252 DE267A#xxx	Processor	1.4-GHz Intel Pentium-M processor with 400-MHz Front Side Bus
	Operating System	Microsoft Windows 2000
	Display	14.1-inch color TFT XGA with 1024 x 768 resolution (up to 16.7M colors internal)
	Cache Memory	1024 KB L2 cache
	Memory	Standard 256-MB 266 MHz SDRAM DDR SDRAM (256-MB SODIMM in slot 1) Maximum 2-GB 266-MHz SDRAM DDR SDRAM (512-MB SODIMM in slots 1 and 2)
	Hard Drive	40-GB 5400 rpm SMART Hard Drive
	Video Memory	32 MB
	Optical Drive	8X DVD
	Graphics	ATI Mobility Radeon 7500 4X AGP graphics controller with 32 MB DDR VRAM
	Audio	Compaq Premier-Sound enhanced stereo audio system
	Communications	56K (V.92) modem, integrated 10/100/1000 NIC
	Pointing Device	Dual pointing devices (both Pointstick and Touchpad)
	Battery	8-cell 4.4 Ah
Warranty	3/3/0	

N620cP140X440VG250 DE266A#xxx	Processor	1.4-GHz Intel Pentium-M processor with 400-MHz Front Side Bus
	Operating System	Microsoft Windows XP Professional
	Display	14.1-inch color TFT XGA with 1024 x 768 resolution (up to 16.7M colors internal)
	Cache Memory	1024 KB L2 cache
	Memory	Standard 256-MB 266 MHz SDRAM DDR SDRAM (256-MB SODIMM in slot 1) Maximum 2-GB 266-MHz SDRAM DDR SDRAM (512-MB SODIMM in slots 1 and 2)
	Hard Drive	40-GB 5400 rpm SMART Hard Drive
	Video Memory	32 MB
	Optical Drive	8X DVD
	Graphics	ATI Mobility Radeon 7500 4X AGP graphics controller with 32 MB DDR VRAM
	Audio	Compaq Premier-Sound enhanced stereo audio system
	Communications	56K (V.92) modem, integrated 10/100/1000 NIC
	Pointing Device	Dual pointing devices (both Pointstick and Touchpad)
	Battery	8-cell 4.4 Ah
Warranty	3/3/0	

Standard Features

N620cP140X440VG252 DE265A#xxx	Processor	1.4-GHz Intel Pentium-M processor with 400-MHz Front Side Bus
	Operating System	Microsoft Windows 2000
	Display	14.1-inch color TFT XGA with 1024 x 768 resolution (up to 16.7M colors internal)
	Cache Memory	1024 KB L2 cache
	Memory	Standard 256-MB 266 MHz SDRAM DDR SDRAM (256-MB SODIMM in slot 1) Maximum 2-GB 266-MHz SDRAM DDR SDRAM (512-MB SODIMM in slots 1 and 2)
	Hard Drive	40-GB 5400 rpm SMART Hard Drive
	Video Memory	32 MB
	Optical Drive	8X DVD
	Graphics	ATI Mobility Radeon 7500 4X AGP graphics controller with 32 MB DDR VRAM
	Audio	Compaq Premier-Sound enhanced stereo audio system
	Communications	56K (V.92) modem, integrated 10/100/1000 NIC
	Pointing Device	Dual pointing devices (both Pointstick and Touchpad)
	Battery	8-cell 4.4 Ah
Warranty	3/3/0	

N620cP140X440VG250 DE264A#xxx	Processor	1.4-GHz Intel Pentium-M processor with 400-MHz Front Side Bus
	Operating System	Microsoft Windows XP Professional
	Display	14.1-inch color TFT XGA with 1024 x 768 resolution (up to 16.7M colors internal)
	Cache Memory	1024 KB L2 cache
	Memory	Standard 256-MB 266 MHz SDRAM DDR SDRAM (256-MB SODIMM in slot 1) Maximum 2-GB 266-MHz SDRAM DDR SDRAM (512-MB SODIMM in slots 1 and 2)
	Hard Drive	40-GB 5400 rpm SMART Hard Drive
	Video Memory	32 MB
	Optical Drive	8X DVD
	Graphics	ATI Mobility Radeon 7500 4X AGP graphics controller with 32 MB DDR VRAM
	Audio	Compaq Premier-Sound enhanced stereo audio system
	Communications	56K (V.92) modem, integrated 10/100/1000 NIC
	Pointing Device	Dual pointing devices (both Pointstick and Touchpad)
	Battery	8-cell 4.4 Ah
Warranty	3/3/0	

Standard Features

N620cP130X430VG252 DE263A#xxx	Processor	1.3-GHz Intel Pentium-M processor with 400-MHz Front Side Bus
	Operating System	Microsoft Windows 2000
	Display	14.1-inch color TFT XGA with 1024 x 768 resolution (up to 16.7M colors internal)
	Cache Memory	1024 KB L2 cache
	Memory	Standard 256-MB 266 MHz SDRAM DDR SDRAM (256-MB SODIMM in slot 1) Maximum 2-GB 266-MHz SDRAM DDR SDRAM (512-MB SODIMM in slots 1 and 2)
	Hard Drive	30-GB 4200 rpm SMART Hard Drive
	Video Memory	32 MB
	Optical Drive	8X DVD
	Graphics	ATI Mobility Radeon 7500 4X AGP graphics controller with 32 MB DDR VRAM
	Audio	Compaq Premier-Sound enhanced stereo audio system
	Communications	56K (V.92) modem, integrated 10/100/1000 NIC
	Pointing Device	Dual pointing devices (both Pointstick and Touchpad)
	Battery	8-cell 4.4 Ah
	Warranty	3/3/0

N620cP130X430VG250 DE262A#xxx	Processor	1.3-GHz Intel Pentium-M processor with 400-MHz Front Side Bus
	Operating System	Microsoft Windows XP Professional
	Display	14.1-inch color TFT XGA with 1024 x 768 resolution (up to 16.7M colors internal)
	Cache Memory	1024 KB L2 cache
	Memory	Standard 256-MB 266 MHz SDRAM DDR SDRAM (256-MB SODIMM in slot 1) Maximum 2-GB 266-MHz SDRAM DDR SDRAM (512-MB SODIMM in slots 1 and 2)
	Hard Drive	30-GB 4200 rpm SMART Hard Drive
	Video Memory	32 MB
	Optical Drive	8X DVD
	Graphics	ATI Mobility Radeon 7500 4X AGP graphics controller with 32 MB DDR VRAM
	Audio	Compaq Premier-Sound enhanced stereo audio system
	Communications	56K (V.92) modem, integrated 10/100/1000 NIC
	Pointing Device	Dual pointing devices (both Pointstick and Touchpad)
	Battery	8-cell 4.4 Ah
	Warranty	3/3/0

Options

		Compaq PN	HP PN
Memory	512-MB (266 MHz) Memory Upgrade	314114-B25	DC890A
	256-MB (266 MHz) Memory Upgrade	269087-B25	DC390A
	128-MB (266 MHz) Memory Upgrade	269086-B25	DC389A
MultiBay Hard Drives	60-GB 5400 rpm SMART Hard Drive	278420-B25	DC894A
	40-GB 5400 rpm SMART Hard Drive	263472-B25	DC365A
	30-GB 4200 rpm SMART Hard Drive	212791-B25	DE882A
MultiBay Storage Devices	24X Combo DVD/CD-RW	269089-B25	DC364A
	24X CD-RW		DC921A
	8X DVD Drive	138230-B25	DC352A
	24X Max CD-ROM	298452-B25	DC351A
	Diskette Drive	226935-B25	DC362A
Other Storage Devices	IBM 1-GB Microdrive (PC card Device)	217390-B25	DC379A
	USB Diskette Drive	230330-B25	DC361A
Wireless Connectivity	802.11b MultiPort Wireless LAN module	283836-001	DC353A
	Bluetooth MultiPort module	228057-B21	DC375A
Expansion Bases	Port Replicator	307648-xx2	DC367A
	Advanced Port Replicator	307651-xx2	DC366A
	External MultiBay	217388-001/B31	DC373A
	Advanced Port Replicator Monitor Stand	274407-B25	DC377A
Power	8-cell primary battery (4.4Ah)	301857-B25	DD487A
Common Power Solutions	MultiBay Battery (8-cell 3.2Ah)	265650-B25	DC358A
	External Battery Charger	135555-xxx	DC357A
	AC Adapter 65W	265602-xxx	DC359A
	Auto Power Adapter/Charger	265649-B25	DC360A
	Aircraft Power Adapter	291370-B25	DC899A
	AC Line Cord (10 ft/3.1 m)	217932-xx2	DC851A
Input Devices	External Enhanced III Keyboard (carbon) USB/PS2 Keyboard	118003-009	DC852A
	Compaq 2 Button Mouse (carbon) USB/PS2 Keyboard 2-button scroll	103180-B23	DC369A
	External 10-Key Numeric Keypad (carbon)	294317-B21	DC854A

Options

Security	Biometric PC Card	146805-B25	DC859A
	Security Cable Lock	294316-B21	DC368A
	Compaq Smart Card PC Card Reader	135646-B25	DC350A

Carrying Cases	Compaq Ultralight Case (nylon)	167336-B21	DC853A
	Compaq Ultralight Case (leather)	242359-B25	DC873A
	Compaq Plus Case	242360-B25	DC345A
	Compaq Professional Case (nylon)	242361-B25	DC874A
	Compaq Professional Case (leather)	242362-B25	DC875A

Monitors	Compaq S9500 CRT Monitor (19-inch, Carbon/Silver)	261615-XXX
	Compaq S7500 CRT Monitor (17-inch, Carbon/Silver)	261606-XXX
	Compaq S5500 CRT Monitor (15-inch Carbon/Silver)	261602-XXX
	Compaq TFT1501 Flat Panel Monitor (15-inch, Carbon/Silver, North America)	301042-003
	Compaq TFT1501 Flat Panel Monitor (15-inch, Carbon/Silver, Outside North America)	P4825D-XXX
	Compaq TFT1701 Flat Panel Monitor (17-inch, Carbon/Silver, North America)	292847-003
	Compaq TFT1701 Flat Panel Monitor (17-inch, Carbon/Silver, Outside North America)	P9019A-XXX
	Compaq V7550 CRT Color Monitor (17-inch, Carbon/Silver)	261611-XXX
	Compaq TFT1720 Flat Panel Monitor (17-inch, Carbon/Silver, North America)	295926-003
	Compaq TFT1720 Flat Panel Monitor (17-inch, Carbon/Silver, outside North America)	D5064D-XXX
	Compaq FT1720M Flat Panel Monitor (17-inch, (Carbon/Silver, includes speaker, USB port, headphone, North America)	301958-003
	Compaq TFT1720M Flat Panel Monitor (17-inch, Carbon/Silver, includes speaker, USB port, headphone, outside North America)	D5064P-XXX
	Compaq TFT1520 Flat Panel Monitor (15-inch, Carbon/Silver, North America)	295925-003
	Compaq TFT1520 Flat Panel Monitor (15-inch, Carbon/Silver, outside North America)	D5063D-XXX
	Compaq TFT1520M Flat Panel Monitor (15-inch, Carbon/Silver includes speaker, USB port, headphone, North America)	301957-003
	Compaq TFT1520M Flat Panel Monitor (15-inch, Carbon/Silver includes speaker, USB port, headphone, outside North America)	D5063P-XXX
	HP P930 CRT Monitor (19-inch, Flat-screen, Carbon/Silver, North America)	302268-003
	HP P930 CRT Monitor (19-inch, Flat-screen, Carbon/Silver, Outside North America)	P909W-XXX
	HP P1130 CRT Monitor (21-inch, Flat-screen, Carbon/Silver, North America)	302270-003
	HP P1130 CRT Monitor (21-inch, Flat-screen, Carbon/Silver, Outside North America)	P4819-XXX

Options

HP L1825 Flat Panel Monitor (18-inch, Carbon/Silver, North America)	303486-003
HP L1825 Flat Panel Monitor (18-inch, Carbon/Silver, Outside North America)	P9021W-XXX
HP L2025 Flat Panel Monitor (20-inch, Carbon/Silver, North America)	303102-003
HP L2025 Flat Panel Monitor (20-inch, Carbon/Silver, Outside North America)	P4831W-XXX
Compaq TFT1825 Flat Panel Monitor (18-inch, Carbon/Silver, North America)	296751-003
Compaq TFT1825 Flat Panel Monitor (18-inch, Carbon/Silver, Outside North America)	P9021A-XXX
Compaq TFT2025 Flat Panel Monitor (20-inch, Carbon/Silver, North America)	285550-003
Compaq TFT2025 Flat Panel Monitor (20-inch, Carbon/Silver, Outside North America)	P4831D-XXX

Memory

Compaq Evo N620C

Standard Memory Plus Optional Memory

Support for up to 2048 MB of DDR SDRAM memory is available with the installation of optional DDR SDRAM Memory Kits.


Memory	Slot 1	Slot 2
256 MB	256 MB	-
512 MB	256 MB	256 MB
512 MB	512 MB	-
768 MB	512 MB	256 MB
1024 MB	512 MB	512 MB
1024 MB	1024 MB	-
1536 MB	1024 MB	512 MB
2048 MB	1024 MB	1024 MB

NOTE: This chart does not represent all possible memory configurations. Due to the non-industry standard nature of some third-party memory modules, we strongly recommend using only Compaq branded memory modules to ensure compatibility.

Following are memory options available from Compaq:

- 1024-MB 266 MHz Memory Upgrade 314114-B25
- 512-MB 266 MHz Memory Upgrade 269087-B25
- 256-MB 266 MHz Memory Upgrade 269086-B25

Storage



Drive Support

System Drive Support	Quantity Supported	Drive Supported
1.44-MB Diskette Drive	1	MultiBay or parallel port cable
DVD/CD-RW Combo Drive	1	MultiBay
CD-RW Drive	1	MultiBay
DVD-ROM Drive	1	MultiBay
Max CD-ROM Drive	1	MultiBay

NOTE: MultiBay support includes the integrated MultiBay, the External MultiBay, and the Advanced Port Replicator MultiBay unless otherwise noted.

Hard Drives

60-GB SMART Hard Drive	2	Dedicated hard drive bay and/or MultiBay
40-GB SMART Hard Drive	2	Dedicated hard drive bay and/or MultiBay
30-GB SMART Hard Drive	2	Dedicated hard drive bay and/or MultiBay

TechSpecs

System Unit	Dimensions (HxWxD)	14.1-inch TFT panel display	1.2 x 12.1 x 9.8 in (3.1 x 30.7 x 25.0 cm)
	Weight	14.1-inch LCD, 1 SODIMM	4.8 lb (2.1 kg) minimum (with weight saver) 5.5 lb (2.45 kg) typical (with MultiBay drive)
		14.1-inch LCD, CD-RW, DVD or CD-ROM, 1 SODIMM	5.5 lb (2.5 kg) *
NOTE: * Height varies depending upon where on the notebook the measurement is made. Weight varies by configuration and components.			
Stand-Alone Power Requirements	Nominal Operating Voltage (Li-Ion)		14.4 V (8-cell)
	Average Operating Power		10.5W
	Peak Operating Power		50W
	Power in suspend mode		< 400 mW
	Power in hibernation mode		< 50 mW
	Power Supply	Rated Input Voltage	
	Rated Input Current		1.6 A
	Rated Frequency		47 to 63 Hz
Temperature	Operating		50° to 95° F (10° to 35° C)
	Non-operating		-4° to 140° F (-20° to 60° C)
Relative Humidity	Operating		10% to 90% relative humidity, non-condensing
	Non-operating		5% to 95% relative humidity, 101.6° F (38.7° C) Maximum wetbulb temperature
Shock	Operating		10 G, 11 ms, half-sine
	Non-operating		60 G, 11 ms, half-sine
Vibration	Operating		0.5 G zero-to-peak, 10 to 500 Hz, 0.25 oct/min sweep rate
	Non-operating		1.0 G, zero-to-peak, 10 to 500 Hz, 0.5 oct/min sweep rate
Maximum Altitude (unpressurized)	Operating		0 to 10,000 ft (0 to 3,048 m)
	Non-operating		0 to 30,000 ft (0 to 9,144 m)
Heat output	Operating (max)		65 W
Industry Standards & Certifications	Blue Angel		No
	UL		Yes
	CSA		Yes
	VDE/TUV		Yes
	Nordic Safety		Yes
	Mexican Safety		Yes
	Poland Compliance		Yes

TechSpecs

14.1-inch Color TFT SXGA+ Display	Dimensions (H x W)	11.22 x 8.46 in (28.5 x 21.5 cm)	
	Diagonal Size	14.1 in (35.7 cm)	
	Mounting	Internal Panel Supports, Side Mounted	
	Number of Colors	Up to 16.8 M	
	Contrast Ratio	150:1	
	Brightness	150 nits typical	
	Pixel Resolution	Pitch	0.204 x 0.204 mm
		Format	1400 x 1050
		Configuration	RGB stripe
	Backlight	Edge Lit	
	Character Display	80 x 25	
	Total Power Consumption	5.1 W	
	Viewing Angle	+15° /-30° Vertical, ± 40° Horizontal	

14.1-inch Color TFT XGA Display	Dimensions (H x W)	11.22 x 8.46 in (28.5 x 21.5 cm)	
	Diagonal Size	14.1 in (35.81 cm)	
	Mounting	Internal Panel Supports, Side Mounted	
	Number of Colors	Up to 16.8 M	
	Contrast Ratio	150:1	
	Brightness	150 nits typical	
	Pixel Resolution	Pitch	0.264 x 0.264 mm
		Format	1024 x 768
		Configuration	RGB stripe
	Backlight	Edge Lit	
	Character Display	80 x 25	
	Total Power Consumption	4.2 W	
	Viewing Angle	+/-35° degrees Horizontal, +15° /-35° Vertical (typical)	

Hard Drives

TechSpecs

60-GB 5400 rpm	MultiBay Drive Adapter	Dimensions (H x W x D)	0.5 x 5.21 x 4.97 in (1.27 x 13.25 x 12.61 cm)
		Weight	0.15 lb (70 g)
	Drive Weight		0.21 lb (95 g)
	Capacity		60 GB
	Height		0.74 in (9.5 mm)
	Width		2.75 in (70 mm)
	Interface		ATA-5
	Transfer Rate	Synchronous (maximum)	100 MB/s (Drive Capability)
		Security	ATA Security
	Seek Time	Single Track	3.0 ms
	(typical reads, including settling)	Average	13 ms
		Maximum	25 ms
	Rotational Speed		5400 rpm
	Logical Blocks		78,140,160
	Operating Temperature	41° to 131° F (5° to 55° C)	
Features	Security	ATA Security	

40-GB 5400 rpm	MultiBay Drive Adapter	Dimensions (H x W x D)	0.5 x 5.21 x 4.97 in (1.27 x 13.25 x 12.61 cm)
		Weight	0.15 lb (70 g)
	Drive Weight		0.21 lb (95 g)
	Capacity		40 GB
	Height		0.74 in (9.5 mm)
	Width		2.75 in (70 mm)
	Interface		ATA-5
	Transfer Rate	Synchronous (maximum)	100 MB/s (Drive Capability)
		Security	ATA Security
	Seek Time	Single Track	3.0 ms
	(typical reads, including settling)	Average	13 ms
		Maximum	25 ms
	Rotational Speed		5400 rpm
	Logical Blocks		78,140,160
	Operating Temperature	41° to 131° F (5° to 55° C)	
Features	Security	ATA Security	

TechSpecs

30-GB 4200 rpm	MultiBay Drive Adapter	Dimensions (H x W x D)	0.5 x 5.21 x 4.97 in (1.27 x 13.25 x 12.61 cm)
		Weight	0.15 lb (70 g)
	Drive Weight		0.22 lb (99 g)
	Capacity		30 GB
	Height		0.74 in (9.5 mm)
	Width		2.75 in (70 mm)
	Interface		ATA-5
	Transfer Rate	Synchronous (maximum)	100 MB/s (Drive Capability)
		Security	ATA Security
	Seek Time	Single Track	2.5 ms
	(typical reads, including settling)	Average	12 ms
		Maximum	23 ms
	Rotational Speed		4200 rpm
	Logical Blocks		58,605,120
	Operating Temperature		41° to 131° F (5° to 55° C)
Features	Security	ATA Security	

Diskette Drive	MultiBay Drive	Dimensions (H x W x D)	0.5 x 5.21 x 4.97 in (1.27 x 13.25 x 12.61 cm)
		Weight	0.51 lb (230 g)
	Diskette Size		3.5 in
	Activity Indicator		On system
	Height		12.7 mm
	Bytes per Sector		512
	Sectors per track	High density	18 (1.44 MB)/15 (1.2 MB)
		Low density	9
	Tracks per side	High density	80 (1.44 MB)/80 (1.2 MB)
		Low density	80
	Read/Write heads		2
	Access Times	Track-to track (high/low)	3 ms/6 ms
		Average (high/low)	94 ms/174 ms
		Settling time	15 ms
		Latency average	100 ms

External AC Adapter	Weight	0.65 lb (0.29 kg) (adapter)	
		0.29 lb (0.13 kg) (power cord)	
	Power Supply (Input)	Operating Voltage	90 to 264 VAC RMS
		Operating Current	1.6 A RMS
		Operating Frequency	47 to 63 Hz AC
		Range	
		Maximum Transient	4/50 kV

TechSpecs

Primary Lithium-Ion Battery Pack (8-cell) Internal	Dimensions (L x W x D)	4.95 x 3.46 x 0.80 in (12.58 x 8.8 x 2 cm)		
	Weight	0.88 lb (0.40 kg)		
	Energy	Voltage	14.4 V	
		Amp-hour capacity	4.6 Ah	
		Watt-hour capacity	63.36 Ah	
	Temperature	Operating	32° to 108° F (0° to 42° C)	
		Non-operating	32° to 140° F (0° to 60° C)	
	Battery Re-Charge Time	System in OFF mode or Standby	2 hours	
		System ON (typical, depending of system power consumption)	2 to 5 hours	
	Lifecycle	80% capacity after 300 full charge/discharge cycles, or 600 half discharge followed by a full charge cycles.		

MultiBay Lithium-Ion Battery Pack (8-cell)	Dimensions (L x W x D)	0.5 x 5.21 x 4.97 in (1.27 x 13.25 x 12.61 cm)		
	Weight	1.03 lb (0.47 kg)		
	Energy	Voltage	14.4 V	
		Amp-hour capacity	3.2 Ah	
		Watt-hour capacity	47.4 Ah	
	Temperature	Operating	32° to 122° F (0° to 50° C)	
		Non-operating	32° to 140° F (0° to 60° C)	
	Battery Re-Charge Time	System in OFF mode or Standby	2 hours	
		System ON (typical, depending of system power consumption)	2 to 5 hours	
	Lifecycle	80% capacity after 300 full charge/discharge cycles, or 600 half discharge followed by a full charge cycles.		

24X DVD/CD-RW Combo Drive	MultiBay Drive	Dimensions (H x W x D)	0.5 x 5.21 x 4.97 in (1.27 x 13.25 x 12.61 cm)	
		Weight	0.74 lb (0.33 kg)	
	Center Hole Diameter	39 cm		
	Disk Diameter	12 cm/8 cm		
	Disk Thickness	1.2 mm		
	Track Pitch	0.74 µm		
	Access Times (typical reads, including settling)	Random	< 150 ms	
		Full-Stroke	< 225 ms	
	Audio Output Level	Line-out	0.7 Vrms	
	Cache Buffer	128 KB/s (minimum)		
	Data Transfer Rate (typical, including settling)	CD-R (24X)	3600 KB/s (150 KB/s at 1X CD rate)	
		CD-RW (10X)	1500 KB/s (150 KB/s at 1X CD rate)	
		CD-ROM (24X)	3600 KB/s (150 KB/s at 1X CD rate)	
		DVD (8X)	10,800 KB/s (1352 KB/s at 1X DVD rate)	
Normal PIO Mode 4 (single burst)		16.6 MB/s		
Start-up Time	< 15 seconds			



TechSpecs

Stop Time < 6 seconds

24X CD-RW Drive	MultiBay Drive	Dimensions (H x W x D)	0.5 x 5.21 x 4.97 in (1.27 x 13.25 x 12.61 cm)
		Weight	0.74 lb (0.33 kg)
	Center Hole Diameter	1.5 cm	
	Disk Diameter	12 cm/8 cm	
	Disk Thickness	1.2 mm	
	Track Pitch	0.74 µm	
	Access Times (typical reads, including settling)	Random	< 150 ms
		Full-Stroke	< 225 ms
	Audio Output Level	Line-out	0.7 Vrms
	Cache Buffer	128 KB	
	Data Transfer Rate (typical, including settling)	CD-R (24X)	3600 KB/s
		CD-RW (8X)	1200 KB/s
		CD-ROM (24X)	3600 KB/s
		Normal PIO Mode 4 (single burst)	16.6 MB/s
Start-up Time	< 15 seconds		
Stop Time	< 6 seconds		

8X DVD-ROM Drive	MultiBay Drive	Dimensions (H x W x D)	0.5 x 5.21 x 4.97 in (1.27 x 13.25 x 12.61 cm)
		Weight	0.66 lb (0.3 kg)
	Center Hole Diameter	1.5 cm	
	Disk Diameter	12 cm/8 cm	
	Disk Thickness	1.2 mm	
	Track Pitch	0.74 µm	
	Access Times (typical reads, including settling)	Random (typical)	< 150 ms DVD Media
		Full-Stroke (typical)	< 225 ms DVD Media
		Random (typical)	< 110 ms CD Media
		Full-Stroke (typical)	< 200 ms CD Media
	Cache Buffer	512 KB/s (minimum)	
	Data Transfer Rate (typical, including settling)	Max 24X CD	3600 KB/s (150 KB/s at 1X CD rate)
		Max 8X DVD	10,800 KB/s (1352 KB/s at 1X DVD rate)
		Normal PIO Mode 4 (single burst)	16.6 MB/s
Start-up Time	< 10 seconds	Single Session CD-ROM	
Stop Time	< 3 seconds		

TechSpecs

24X CD-ROM Drive	MultiBay Drive	Dimensions (H x W x D)	0.5 x 5.21 x 4.97 in (1.27 x 13.25 x 12.61 cm)
		Weight	0.50 lb (0.22 kg)
	Applicable Disk	CD-ROM (Mode 1, 2 and 3), CD-XA ready (Mode 2, Form 1 and 2), CD-I ready (Mode 2, Form 1 and 2), CD-R (read only), CD Plus, Photo CD (Single and Multi-session), CD-Extra, Video CD, CD-WO (fixed packets only), CD-Bridge	
	Center Hole Diameter	15 mm	
	Disk Diameter	12 cm, 8 cm	
	Disk Thickness	1.2 mm	
	Track Pitch	1.6 µm	
	Access Times (typical reads, including settling)	Random	< 150 ms
		Full-Stroke	< 300 ms
	Audio Output Level	Line-out	0.7 Vrms
	Cache Buffer	128 KB	
	Data Transfer Rate (typical, including settling)	Sustained (16X)	2400 KB/s
		Variable	1500 to 3600 KB/s (10X to 24X)
		Normal PIO Mode 4 (single burst)	16.66 MB/s
	Start-up Time	< 8 seconds	
	Stop Time	< 4 seconds	

MultiBay Diskette Drive	MultiBay Drive	Dimensions (H x W x D)	0.5 x 5.21 x 4.97 in (1.27 x 13.25 x 12.61 cm)
		Weight	0.51 lb (230 g)
	Diskette Size	3.5 in	
	Height	12.7 mm	
	Bytes per Sector	512	
	Sectors per track	High density	18 (1.44 MB)/15 (1.2 MB)
		Low density	9
	Tracks per side	High density	80 (1.44 MB)/80 (1.2 MB)
		Low density	80
	Read/Write heads	2	
	Access Times	Track-to track (high/low)	3 ms/6 ms
		Average (high/low)	94 ms/174 ms
		Settling time	15 ms
		Latency average	100 ms

TechSpecs

Audio	Features	SoundMAX
	Wavetable Synthesis	
	# of Voices	Up to 1024 (CPU dependent)
	# of MIDI Channels	16
	Max. Sound Set Size	Unlimited (host RAM dependent)
	Sound Set Formats	DLS (Level 1), XGLite
	Bundled GeneralMIDI Sound Set(s)	1.2 MB XGLite
	Built-In Effects	Reverb and Chorus
	Sound Blaster PRO Emulation	Yes
	3D Positioning / Environments	
	Formats Supported	I3DL2 / DS3D 7 / EAX 2 / A3D 1
	Environmental Acoustics	EnvironmentFX (EAX compatible)
	Additional 3D APIs	MacroFX / ZoomFX
	Standard HRTFs	2 Channel
	Hardware	
	Implimentation	AC97 CODEC
	Audio Signal Link to CPU	Audio CODEC (AC) link
	Full Duplex	Yes
	Stereo Inputs	Line In - 20K Impedance
	Mono Inputs	Microphone - 20K Impedance
	Stereo Outputs	Analog, S/PDIF from Port Rep
	Audio Output Quality	
	Frequency Response	20 Hz - 20 kHz
	Signal to Noise Ratio	>94dB
	Total Harmonic Distortion	0.01%
	Noise Floor	-120dB
	Play/Record Sampling Rate(s)	7 kHz - 48 kHz
	AD/DA Resolution	16 bit
	Speakers	
	Amplifier Power	2-Watts RMS
	Speaker Impedance	4-Ohms

802.11b MultiPort Module	Form Factor	Compaq "MultiPort"	
	Weight	0.22 lb (100 g) (maximum)	
	Operating Temperature	14° to 149° F (-10° to 65° C), operating	
	Storage Temperature	-40° to 176° F (-40° to 80° C), non-operating	
	Humidity	Operating	10% to 90%
		Non-operating	5% to 95%
	Altitude	Operating	15,000 ft (4,572 m)
		Non-operating	40,000 ft (12,192 m)
	Plug and Play	USB 1.1 compliant	
		Microsoft Windows Plug and Play compliant	

TechSpecs

RF Network Standard	IEEE 802 Part 11b (802.11b)
Frequency Band	2.4000 to 2.4835 GHz 2.4465 to 2.4835 GHz (France) 2.4000 to 2.4697 GHz (Japan)
Number of Selectable Sub-channels	Worldwide Certification United States (FCC) 11 France (FR) 4 Japan (JP) 14 Other countries 13
Data Rates	1, 2, 5.5, 11 Mbps
Antenna type	Internally integrated within module (with special polarization diversity)
WEP Security	64-bit encryption keys compliant to IEEE 802.11 128-bit encryption key compliant to IEEE 802.11 Ability to enter keys manually or via pass-phrase
Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Points Required)
Modulation Technique	Direct Sequence Spread Spectrum: DBPSK, DQPSK, CCK
Receiver Sensitivity – Bit Error Rate (1E-5)	11 Mbps: -85 dBm 5.5 Mbps: -87 dBm 2 Mbps: -91 dBm 1 Mbps: -94 dBm
Maximum Receive Level	-4 dBm
Output Power (approximately)	18 dBm
Operating Voltage	5V power operation
Power Management	Keystroke Fn+F2 Power On/Off control
Power Consumption	Transfer mode: < 600 mA, maximum Receive mode: > 400 mA, maximum Standby mode: > 1 mA, maximum
Transmit Power	10 to 100mW It is preferable to have the user configurable output power to save battery life for laptop users or in high AP coverage areas
Power Saving Option	802.11 Compliant Power Saving Power Saving Mode selectable through the configuration utility ACPI compliant power management
Media Access Protocol	CSMA/CA (Collision Avoidance) with ACK
OS Support	Microsoft Windows XP Professional and Home Editions Microsoft Windows 98/98SE Microsoft Windows 2000 Microsoft Windows Millennium
Protocols Supported	TCP/IP IPX/SPX UDP
LED Activity	Flashing LED – AP Search Mode Solid LED – On LED Off – Power Off

TechSpecs

Throughput, Data Rate and Operating Distance	Throughput	Data Rate	Operating Distance
	> 4.5 Mbps	11 Mbps	<ul style="list-style-type: none"> ● 1000 feet – Open sight ● 100 feet – Closed space (Steel Space)
	> 2 Mbps	5.5 Mbps	<ul style="list-style-type: none"> ● 1100 feet – Open sight ● 200 feet – Closed space (Steel Space)
	> 700 Kbps	1 Mbps	<ul style="list-style-type: none"> ● 1200 feet – Open sight ● 300 feet – Closed space (Steel Space)

Bluetooth MultiPort Module	Form Factor	Compaq "MultiPort"		
	Bluetooth	1.1 Compliant		
	Dimensions	2.2 x 6.6 x 0.55 in (5.6 x 16.7 x 1.4 cm)		
	Weight	0.22 lb (100 g) (maximum)		
	Temperature	Operating	-50° to 104° F (10° to 40° C)	
		Non-operating	-4° to 140° F (-20° to 60° C)	
	Humidity	Operating	10 to 90%	
		Non-operating	5 to 95%	
	Altitude	Operating	0 to 10,000 ft (3,048 m)	
		Non-operating	0 to 30,000 ft (9,144 m)	
	Plug and Play	USB 1.1 compliant		
		Microsoft Windows Plug and Play compliant		
	Frequency Band	2.4000 to 2.4835 GHz		
	Number of Available Channels	79 (1 MHz) available channels		
	Data Rates and throughput	1 Mbps		
		Synchronous Connection Oriented links up to 3, 64 kbps, voice channels		
Asynchronous Connection Less links 723.2 kbps/57.6 kbps asymmetric or 433.9 kbps symmetric				
Antenna type	Internally integrated within module (with special polarization diversity)			
Range	328 ft (100 m)			
Profile Support	General Access Profile			
	Service Discovery Application Profile			
	Serial Port Profile			
	Generic Object Exchange Profile			
	File Transfer Profile			
	Synchronization Profile			
	Dial-Up Networking Profile			
	LAN Access Profile			
	Object Push Profile			
	Usage Models	Service Discovery (determine what Bluetooth devices are within range and support authorization)		
Synchronization				
PDAs to PCs Portable to Desktop				
File Transfer	File and directory browsing and navigation on another Bluetooth device			
	File copying			
	Object manipulation – including add, delete, create new folders etc.			
	Wireless link to Corporate LAN using several Bluetooth devices sharing			

TechSpecs

	the same Access Point: Corporate email, network neighborhood, access to LAN applications, file transfer, ftp, Internet browsing, etc, using TCP/IP Wireless link to WAN through cell phone GSM/SMS, PCS, PHS, DECT, RAM, ARDIS, CDPD, etc. Agnostic to WAN technology Send/receive SMS messages Wireless link to Printer Adhoc peer to peer networking (two computers) or Personal Area Networking (PAN) using NDIS (< 7 computers) Adhoc Bluetooth Pico-networking (point to multi-point) Object Push – Business card or appointment exchange
Transmit Power	< 20 dBm (Bluetooth Class 1)
Receive Sensitivity	Better than –70 dBm at 0.1 % raw bit error rate
Link Topology	Point to Point, Multipoint Pico Nets up to 7 slaves
Security	Full support of Bluetooth Security Provisions
Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Points Required)
Power Requirement	Peak < 1500 mW Average < 500 mW Standby < 250 mW
Power Management	Windows ACPI, and USB Bus Support Keystrokes Fn+F2 Power On/Off control Self configurable to optimize power conservation in all operating modes, including Standby, Hold, Park, and Sniff
OS Support	Microsoft Windows XP Professional and Home Editions Microsoft Windows 98/98SE Microsoft Windows 2000 Microsoft Windows Millennium
Protocols Supported	TCP/IP IPX/SPX UDP
LED Activity	Solid Blue LED – On LED Off – Power Off
Certifications	All necessary regulatory approvals for countries we support including FCC (47 CFR) Part 15C, Section 15.247 & 15.249 ETS 300 328, ETS 300 826 Low Voltage Directive IEC950 UL, CSA, and CE Mark

TechSpecs

56K (V.92) Modem	Form Factor	Mini-PCI Type III per Specification
	OS Support (with all released Service Packs)	Microsoft Windows XP Professional and Home Editions, Microsoft Windows 98 (Gold, SE), Windows NT 4.0, Windows 2000, Windows Millennium Edition, DOS Application Support under Windows
	Power Management Support	APM Revision 1.2, ACPI
	Approvals/Certifications	UL, CSA, NEMKO, CCIB, Industry Canada, FCC Part 68, CTR21, FCC Part 15 Class B, Canadian ICES-003 Class B, C.I.S.P.R.22, Australian ACA, CE Mark, Other Countries
	Data Mode Capabilities	V.90, V.92 (a-law, mu-law) V.8bis V.80 V.44, V42.bis, MNP5 (Compression) V.42 (LAPM, MNP2-4) (Error Correction) V.34 (file date: 10/96) Optional symbol rates: 2800, 3429 Asymmetric Symbol rates Synchronous primary channel data signaling rates: 3600, 31200 Automatic rate re-negotiation V.32bis V.32 V.23 V.22bis V.22 V.21 Bell 212A Bell 103J
	Fax Mode Capabilities	TIA/EIA-578-B (Class 1) T.30, T.4 (Group 3) V.17 V.29 V.27ter V.21 Channel 2
	Command Set	V.250 (Partial) TIA-602 Identification: +GMI, +GMM, +GMR Port control: +IPR, +ICF, +IFC, +ILRR Modulation: +MS, +MR, +MA Error control: +ES, +ER, +EB, +ESR, +ETBM Data compression: +DS, +DR V.251

TechSpecs

Integrated 10/100/1000 NIC	NIC Device Driver Name	Broadcom NetXtreme Gigabit Ethernet
	Ethernet Features	10 Mbit/s operation (10BASE-T; IEEE 802.3j; IEEE 802.3 clauses 13-14) 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 1000 Mbit/s operation (1000BASE-T; IEEE 802.3z and 802.3ab; IEEE 802.3 clauses 34-42) Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s IEEE 802.1p QoS (Quality of Service) Support IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable)
	Performance Features	TCP / IP / UDP Checksum Offload (configurable) Microsoft Large Send Offload (configurable) TCP Segmentation Offload CPU Task Offload Adaptive Interrupts
	Power Management	ACPI 1.1a compliant -- multiple power modes Situation-sensitive features reduce power consumption NIC Battery Saving Mode (enabled by default)
	Manageability	Wake-on-LAN from all Power-Managed States (configurable; Magic Packet and Microsoft Wake-Up Frame) PXE 2.0 Remote Boot Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30)) Comprehensive diagnostic and configuration software suite Cable Analyzer
	Drivers Available	Windows XP Windows 2000 Windows NT 4.0 Windows 98 Linux kernel versions 2.2 and 2.4

© Copyright 2003-2004 Hewlett-Packard Development Company, L.P.
The information contained herein is subject to change without notice.

Microsoft, Windows and Windows NT are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. Pentium, the Intel Inside Logo, and SpeedStep are registered trademarks or trademarks of Intel Corporation in the U.S. and/or other countries. Bluetooth is a trademark of Bluetooth SIG, Inc., in the U.S. and other countries. BatteryMark is a trademark of Ziff Davis Publishing Holdings Inc., and affiliate of eTesting Labs Inc., in the U.S. and other countries. All other product names mentioned herein may be trademarks of their respective companies.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.